

















Technical information Graphic

Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information

Included in EN 15114		Use classification		EN 10874	33 Heavy commercial
		Weight	Rolls	ISO 8543	3,0 kg/m ²
		Thickness	Rolls	ISO 1765	2,2 mm
			Tiles		2,7 mm
		Roll dimension	Width	EN 426	2000 mm
			Length		25 m
		Tile dimension		EN 994	500 x 500 mm. 20 pcs/box, 5 sqm
		Castor Chair		EN 985	Continous use
		Body Voltage		EN 1815**	Fulfilled
		Thermal resistance		ISO 8302	Suitable for underfloor heating
		Impact sound insulation*		EN ISO 10140	12 dB
		Airborne sound absorption*		EN ISO 354	0,05
		Colour fastness to light*		EN ISO 105-B02	8
	Dimension stability	Rolls	ISO 2551	Fulfilled	
		Tiles	EN 986	Fulfilled	
Additional tests		Anti slip property		DIN 51130	R9
		Friction		EN 13893	> 0,3
		Pendulum		EN 13036-4	88-93
		Reaction to fire		EN 13501-1	B _{fl} -s1
		Critical radiant flux		ASTM E 648	Class 1
		Smoke density		ASTM E 662	< 450
		Emission		EN ISO 16000-10	< 50 µg/m ² h
Certifications		CE certificate		EN 14041	No 0402-CPD-419001
		Floor Score certificate	Rolls	SCSEC-10.2-2007	SCS-FS-02007
			Tiles		SCS-FS-02240
	Classification	Rolls		CSTB	U3s P3 E1/2 C1 No 12/15-1698
		Tiles			U3s P3 E1/2 C1 No 12/15-1698

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.



Bolon Flooring is recyclable



SCS FSC CERTIFICATION SYSTEMS
SCS-140207

SCS FSC CERTIFICATION SYSTEMS
SCS-140207