
























Technical information Now

Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information

Included in EN 15114		Use classification	EN 10874	32 General commercial
		Weight	Rolls ISO 8543	2,8 kg/m ² 3,8 kg/m ²
		Thickness	Rolls ISO 1765	2,4 mm 2,9 mm
		Roll dimension	Width EN 426	2000 mm
		Tile dimension	Length EN 994	25 m
		Castor Chair	EN 985	500 x 500 mm. 20 St/Box, 5 m ²
		Body Voltage	EN 1815**	Continuous use
		Thermal resistance	EN 1815**	Fulfilled
		Impact sound insulation*	ISO 8302	Suitable for underfloor heating
		Impact sound insulation*	EN ISO 10140	12 dB
		Airborne sound absorption*	EN ISO 354	0,05
		Colour fastness to light*	EN ISO 105-B02	8
		Dimension stability	Rolls ISO 2551 Tiles EN 986	Fulfilled Fulfilled
Additional tests		Anti slip property	DIN 51130	R9
		Friction	EN 13893	> 0,3
		Pendulum	EN 13036-4	97-101
		Reaction to fire	EN 13501-1	B _{fl} -s1
		Critical radiant flux	ASTM E 648	Class 1
		Smoke density	ASTM E 662	< 450
		Emission	EN ISO 16000-10	< 20µg/m ² h
Certifications		CE certificate	EN 14041	No 0402-CPD-419001
		Floor Score certificate	Rolls SCSEC-10.2-2007 Tiles	SCS-FS-02007 SCS-FS-02240
		Classification	Rolls CSTB Tiles	U3 P2 E1/2 C1 No 12/14-1691 U3 P2 E1/2 C1 No 12/14-1691

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.

