















Technical information Bolon By Missoni

Construction: Woven vinyl flooring, product standard EN 15114

Included in EN 15114		Use classification		ISO 10874	33 Heavy commercial
		Weight	Rolls Tiles	ISO 8543	2,9 kg/m ² 3,9 kg/m ²
		Thickness	Rolls Tiles	ISO 1765	2,5 mm 3,0 mm
		Roll dimension	Width Length	EN 426	2000 mm 25 m
		Tile dimension		EN 994	500 x 500 mm. 20 pcs/box, 5 sqm
		Castor Chair		EN 985	Continuous use
		Body Voltage		EN 1815**	Fulfilled
		Thermal resistance		ISO 8302	Suitable for underfloor heating
		Impact sound insulation*		EN ISO 10140	11 dB
		Airborne sound absorption*		EN ISO 354	0,05
		Colour fastness to light*		EN ISO 105-B02	8
		Dimension stability	Rolls Tiles	ISO 2551 EN 986	Fulfilled Fulfilled
	Additional tests		Anti slip property		DIN 51130
		Friction		EN 13893	> 0,3
		Pendulum		EN 13036-4	94-95
		Reaction to fire		EN 13501-1	B _{fl} -s1
		Critical radiant flux		ASTM E 648	Class 1
		Smoke density		ASTM E 662	< 450
		Emission		EN ISO 16000-10	<50 µg/m ² h
		CE certificate		EN 14041	No 0402-CPD-419006
		Floor Score certificate	Rolls Tiles	SCSEC-10.2-2007	SCS-FS-02007 SCS-FS-02240
		Classification	Rolls Tiles	CSTB	U3 P2 E1/2 C1 No 12/14-1692 U3 P2 E1/2 C1 No 12/14-1692

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.



Bolon Flooring
is recyclable



SCS GLOBAL CERTIFICATION SYSTEMS
SCS-140007