

工匠系列技术信息

建筑: 编织乙烯地板, 产品标准 EN 15114

www.bolon.com 查看更新信息

包含于 EN 15114

	使用分类		EN 10874	33 重型商用
	重量	卷地板 瓷砖	ISO 8543	2.9 kg/m ² 3.9 kg/m ²
	厚度	卷地板 瓷砖	ISO 1765	2.5 mm 3.0 mm
	卷地板尺寸	宽度 长度	EN 426	2000 mm 25 m
	瓷砖尺寸		EN 994	500 x 500 mm, 20 pcs/box, 5 sqm
	脚轮椅		EN 985	连续使用
	体电压		EN 1815**	已满足
	耐热		ISO 8302	适用于地暖
	冲击隔音*		EN ISO 10140	11 dB
	空气声音吸收		EN ISO 354	0,05
	对光的色牢度*		EN ISO 105-B02	8
	尺寸稳定性	卷地板 瓷砖	ISO 2551 EN 986	已满足 已满足

附加测试

	防滑属性		DIN 51130	R10
	摩擦		EN 13893	> 0.3
	摇摆		EN 13036-4	94-95
	对火的反应		EN 13501-1	B _{fl} -s1
	关键辐射量		ASTM E 648	等级 1
	烟浓度		ASTM E 662	< 450
	排放		EN ISO 16000-10	<50 µg/m ³ h

认证

	CE 证书		EN 14041	No 0402-CPD-419001
	地板得分证书	卷地板 瓷砖	SCSEC-10.2-2007	SCS-FS-02007 SCS-FS-02240
	分类	卷地板 瓷砖	CSTB	U3 P2 E1/2 C1 No 12/14-1692 U3 P2 E1/2 C1 No 12/14-1692

* 典型值

** EN 1815 替代 ISO 6356

某些系列为设计保护。



Bolon 地板为可循环利用

SCS 认证

SCS 认证