

Bolon By Missoni技术信息

材料结构: 乙烯编织地板, 产品标准 EN 15114

包含于 EN 15114		使用空间分类	ISO 10874	33 高流量商用空间
		重量	卷材 方块	ISO 8543 2.9 kg/m ² 3.9 kg/m ²
		厚度	卷材 方块	ISO 1765 2.5 mm 3.0 mm
		卷材尺寸	宽度 长度	EN 426 2000 mm 25 m
		方块尺寸	EN 994	500 x 500 mm. 20 pcs/盒, 5 sqm
		办公椅滚轮	EN 985	可连续性使用
		人体静电	EN 1815**	合格
		热能阻隔	ISO 8302	适用于地暖系统
		冲击隔音*	EN ISO 10140	11 dB
		空气声音吸收	EN ISO 354	0.05
		光线色牢度*	EN ISO 105-B02	8
		尺寸稳定性	卷材 方块	ISO 2551 EN 986 合格 合格

附加测试		防滑属性	DIN 51130	R9
		摩擦检测	EN 13893	> 0.3
		摆动检测	EN 13036-4	94-95
		防火等级	EN 13501-1	B _{fl} -s1
		临界热辐射量	ASTM E 648	Class 1
		烟雾密度	ASTM E 662	< 450
		排放	EN ISO 16000-10	<50 µg/m ³ h
		CE 证书	EN 14041	No 0402-CPD-419006
		FloorScore 证书	卷材 方块	SCSEC-10.2-2007 SCS-FS-02007 SCS-FS-02240
		分类	卷材 方块	CSTB U3 P2 E1/2 C1 No 12/14-1692 U3 P2 E1/2 C1 No 12/14-1692

* 典型值

** EN 1815 替代 ISO 6356

某些系列为设计保护。



Bolon 地板为可回收利用